ProTankless™ GWH 425 EF

Features:

- Electronic ignition
- ► 80% average efficiency
- Built-in power vent for horizontal through-wall venting
- Venting: 4" single-wall stainless or galvanized
- Modulating gas valve constant temperature at varying flow rates
- Available in Natural Gas (NG) or Liquid Propane (LP)
- 15-Year warranty

Safety and Ingenuity – Guaranteed.




The 425 EF is the ideal water heater when the installation calls for horizontal venting.

GWH 425 EF Technical Specifications	
Power Input	Natural Gas: 28,000 - 130,000 Btu
	LP Gas: 28,000 - 125,000 Btu
Minimum Flow to Activate	0.5 gallons per minute (gpm
Flow Rates	45°F rise @ 4.6 gpm 55°F rise @ 3.8 gpm 65°F rise @ 3.3 gpm 77°F rise @ 2.7 gpm 90°F rise @ 2.3 gpm
Energy Factor	NG: .78 LP: .81
Thermal Efficiency	NG: 80% LP: 82%
Dimensions	29.75" h x 18.25" w x 8.75"
Weight	44 lbs.
Modulating Gas Valve	Yes
Ignition	Electronic
Required Accessory	Horizontal Vent Terminator (Part # FXHOOD)


Solid Copper Heat Exchanger

Stainless Steel Burners

Temperature Control Knob



GWH 425 EF Installation SpecificationsGas Connection½" Male NPTWater Connections½" Male NPTNG Gas PressureMinimum: 7" WC
Maximum: 14" WCLP Gas PressureMinimum: 11" WC
Maximum: 14" WCWater PressureMinimum: 30 PSI
Maximum: 150 PSIElectrical Supply120VAC – plugs in




Model GWH 425 EF Venting Configurations

Approved Vent Terminal

(FXHOOD or other approved terminal) The FXHOOD is design approved with the 425 EF and has a built-in back draft flapper to prevent negative air from freezing the unit.

GWH 425 EF Installation ClearancesTop (A)12"Front (B)4"Back0"Sides4"Floor (C)12"



4"single wall venting only. Use stainless steel (AL29-4C) or galvanized pipe of 26 minimum gauge must be used. Each connection must be properly sealed.



BBT NORTH AMERICA CORPORATION Bosch Group

Bosch Water Heating 340 Mad River Park Waitsfield, VT 05673

Telephone: 866.642.3198 www.boschpro.com

